

Fuel and Lubricants Cartridge 1645

Separation : Liquid/Solid
Equipment : FILTER
Media : disposable
Technical

Product references

L 1645

Application:

Filtration of fuels and lubricants
specifically for diesel engines

Technical data:

Functional

Filtration grade: 5 μ , 10 μ or 20 μ @ 90%
(cartridge new)

Maximum Flow Rat : 600 l/h for oil SAE 30 @ 80°C.
Working temperature : < 150°C

Geometrical

External diameter : 112mm +/- 3
Height : 400mm +/- 3
Area : 0.14m²

Maintenance:

The cartridge must be regularly changed.
The quantity of matter accumulated is very important,
so, supply a hook to leave the cartridges.

Life Span:

The cartridges have a life span of maximum 6000 h.
This life span is function of the chemical treatment
with a catalyst of polymerization.

Additional information:

Protection of employees:

Avoid the contact with the cartridges saturated
with oil products.
Allergic reactions or others can be noted.

Destruction:

Accordingly to the French environmental code, article R 541-8, annex Two the **LEFCO**[®] oil cartridges are part of the categories 15.02.02.

A special plastic bag is provided to wrap up the used cartridge. These cartridges must be sending towards an authorized treatment center. A list of these centers could be indicated on demand.