

# Fuel and Lubricants Cartridge 1240C

Separation : Liquid/Solid  
Equipment : FILTER  
Media : disposable  
**Technical**

## Product references

LF 1240 C

## Application:

Filtration of oil, lubricants and cutting oils  
Filtration of fuel for diesel engines

## Technical data:

### Functional

Filtration grade: 5µ @ 90%  
(cartridge new)

Flow Rate : 360 l/h for oil SAE 30 @ 60°C.  
Flow Rate : 230 l/h for fuel, gas-oil, gasoline  
Working temperature : < 150°C

### Geometrical

External diameter : 105mm +/- 3  
Internal diameter : 27mm +/- 2  
Height : 305 mm -0/+6

## Maintenance:

The cartridge must be regularly changed.  
The quantity of matter accumulated is very important,  
so, supply a hook to leave the cartridges

## Life Span:

The cartridges have a life span of maximum 1000 m<sup>3</sup>

## Water Absorption :

One cartridge has an absorption capacity of approximately  
0.5 liter of water, **which will clog up the cartridge.**

## Protection of employees:

Avoid the contact with the cartridges saturated  
with oil products.  
Allergic reactions or others can be noted.

## Destruction:

Accordingly to the French environmental code, article R 541-8, annex Two the **LEFCO**® oil cartridges are part of the categories 15.02.02.

A special plastic bag is provided to wrap up the used cartridge. These cartridges must be sending towards an authorized treatment center. A list of these centers could be indicated on demand.